

(19)

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 104 161 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
30.05.2001 Bulletin 2001/22

(51) Int Cl.7: H04N 1/00

(21) Application number: 00310090.6

(22) Date of filing: 14.11.2000

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR  
Designated Extension States:  
AL LT LV MK RO SI

(72) Inventor: **Salgado, David L.**  
Victor, NY 14564 (US)

(74) Representative: **Rackham, Stephen Neil**  
**GILL JENNINGS & EVERY,**  
Broadgate House,  
7 Eldon Street  
London EC2M 7LH (GB)

(30) Priority: 24.11.1999 US 448805

(71) Applicant: **Xerox Corporation**  
Rochester, New York 14644 (US)

## (54) Measuring scanner registration

(57) A registration detection system determines a registration problem in an apparatus having an optical reader (22) adapted to scan a document. The system

comprises a test pattern generator (24) and a mixer (26) for combining an output of the test pattern generator (24) with an output of the optical reader (22).




FIG. 3

EP 1 104 161 A2

## Description

[0001] The present invention relates to document processing machines and, more particularly, to document scanning requiring document registration.

[0002] Referring to Fig. 1, there is shown a perspective view of a document processing apparatus 10. The apparatus 10 could be any suitable type of document processing apparatus, such as a copier, a facsimile machine, a scanner, a computer printer, or a multifunction device having two or more functions. Referring also to Fig. 2, in this embodiment the apparatus 10 is a copier which includes an original document feed system 11 and a copy document feed system 13. A scanner or image obtainer 12 is provided under a transparent glass platen 15. The scanned information from an original document fed through the original document feed system 13 is imaged onto paper selected from paper trays 14 or 16. Paper selected from either of the paper trays 14, 16 is moved by the copy document feed system 13 through the apparatus 10 by means of various belts 18 and rollers 19 schematically depicted in Fig. 2. The original document feed system 11 also comprises suitable belts and rollers for automatically moving original documents through the document system.

[0003] Various document systems require that an automatic document handling apparatus within the system operate so as to align a particular edge of a document with a given coordinate. For example, in an x-y coordinate system this could be the coordinates 0,0, on a copier platen where the scanner or copier optics have also been aligned to begin imaging at the 0,0 coordinates on the copier platen. This process of aligning the document relative to a given coordinate is known as document registration. In a manual copying operation, an original document is registered by the user with ruler markings along the sides of the platen. In systems having automatic document handling systems document registration is automatic and is generally accomplished by the use of various belts, rollers and sensors situated along the document path. If the original document is not properly registered then undesirable dark borders and shadow images may appear on the copy. Thus, while proper document registration is critical to the operation of a document processing system it is yet one of the most difficult to achieve features of an automatic document handling system. An automatic document handling system must rapidly and accurately register each original document. In general, the document registration accuracy desired is on the order of one millimeter. In addition, improper registration due to document skewing by the paper rollers can damage original documents and affect the further automatic operation of the document handler.

[0004] Various methods exist for measuring and aligning the registration of documents within a document handling system. For example, US-A-4,831,420 discloses a system for setting registration using preprinted and specially constructed test. The test docu-

ments are comprised of identifying registration marks identifying registration position and a registration cutout window. Setting the registration involves registering and copying a preprinted test sheet using the document feeder in its initial and unadjusted, registration setting. The copy produced is then compared with the original test document by placing the copy of the test document under the original test document so that the test patterns on the copy are visible through the cutout window. Thus, the test patterns on the copy may be compared with the test patterns on the original revealing the amount of registration adjustment required.

[0005] Other methods that exist for setting document registration also involve the use of expensive, specially constructed, preprinted master test documents for a variety of paper sizes and test patterns. Other disadvantages to the preprinted master test document approach are lead times for printing the various test documents required and storage by the user, whether on site or by the field service engineer.

[0006] A registration detection system for measuring document registration in an apparatus having an optical reader adapted to scan a document. The system comprising a test pattern generator and a mixer for combining an output of the test pattern generator with an output of the optical reader.

[0007] A method for determining if a scanner registration problem exists in an apparatus adapted to scan a document, the method comprising the steps of: scanning a first image; combining a first test pattern with the scanned first image; and providing informative feedback resulting from the step of combining the first test pattern with the scanned first image.

[0008] A scanner device registration measuring system for determining a scanner registration problem in a scanner device. The system comprising a test pattern generator, an input document scanning device, and an image transfer system.

[0009] A particular embodiment in accordance with this invention will now be described with reference to the accompanying drawings; wherein:-

Fig. 1 is a perspective view of a conventional document processing apparatus;

Fig. 2 is a schematic view of paper paths within the paper processing apparatus shown in Fig. 1;

Fig. 3 is a block diagram of a document registration system incorporating features of the present invention;

Fig. 4 is a flowchart of one method for measuring document registration using the system shown in Fig. 3;

Fig. 4a is an exploded flowchart of the one method for measuring document registration shown in Fig.

4; and

Fig. 5 is a schematic representation of combining a printed test pattern with the same test pattern residing in memory.

[0010] Referring now to Fig. 3 there is shown a block diagram of one embodiment of a document registration measuring system 21 incorporating features of the present invention. The system 21 is generally intended to be used for registering documents in a document processing apparatus such as described above with reference to Figs. 1 and 2 (e.g.: a copier, a facsimile machine, a computer printer, a scanner, or a multifunction device). The system 21 generally comprises an optical scanner 22, a test pattern generator 24, test pattern memory 25, a combiner 26, and a selector 29 for selecting the output of the test pattern generator 24 or combining the output with information provided by the optical scanner 22.

[0011] The optical scanner 22 generally comprises any suitable system for detecting light and translating it into electric signals in order to reproduce or sense and subsequently transmit an image. This is usually accomplished by the use of various photoelectric devices, such as a photoelectric cell. Optical sensing typically involves moving a finely focussed beam of light across a document and recording variations in intensity or another property of light as the light is transmitted or reflected from an original document. Alternatively, any suitable photocopying, processes that use chemical, electrical, or photographic techniques to copy printed or pictorial matter may be used.

[0012] The test pattern generator 24 generally comprises an integrated circuit board 24a generally capable of image processing functionality such as magnification, screening, contrast control, and test pattern generation. Generally, the test pattern generator is controlled by user input from the user interface 8 (see Fig. 1), but could also be controlled by onboard switches or an external interface such as a portable service workstation.

[0013] The test pattern memory 25 generally comprises a data storage medium capable of storing various test patterns. The medium may be any suitable data medium such as Read-Only-Memory chips located on board the test pattern generator 24, or within a software program.

[0014] The selector 29 for selecting the test pattern generator is represented symbolically as a switch. However, any suitable means for selecting between the output of the test pattern generator 24 or combining the output with the output of the optical scanner 22 in the combiner 26 may be used.

[0015] In general, the combiner 26 comprises a combiner capable of mixing the input from the optical scanner 22 with the input from the test pattern generator 24 so as to overlay the test pattern on the copy. This is represented graphically in Fig. 5. Test pattern TPIa is printed on hardcopy 70. Hardcopy 70 is scanned and com-

bined with test pattern TPIb from test pattern generator 24 in combiner 26. The output from the combiner 26 is hardcopy 80 which shows TPIb overlying TPIa. The difference between the patterns represents the registration error. In addition, the combiner 26 may digitally mix the input signals to provide registration information and instruction to correct registration error such as shown in 80b. The combiner may be any suitable combiner that is compatible with the document processing apparatus and the test pattern generator and could include a digital mixing circuit. The combiner 26 may use any suitable method for combining the output of the test pattern generator 24 with the output of the optical scanner 22.

[0016] Referring also to Fig. 4 there is shown a flow-chart of one method for measuring document registration using the system shown in Fig. 3. In short, the user merely prints 52a, scans 52b, and combines 52c, to determine document registration. These steps are further illustrated in Fig. 4a. The user can start by selecting various parameters unique to the system under test via the user interface 8 (see Fig. 1) or an external interface such as portable workstation. These parameters may include fast or slow scan size scales and copy document size 53. Next the operator can select the desired test pattern 54. The test pattern may be crosshair, edged, edged crosshair, grid, edged grid, or any suitable type of test pattern appropriate to the system under test. The operator can then direct the system to print 56 a copy of the test pattern directly to the output (i.e., switch 29 in Fig. 3 is in the 29a position). A test pattern so produced is now designated as the master test pattern document. The master test pattern document is loaded into the document handling system 11 of copier 10 or manually placed on the platen 12 (see Fig. 1). The master test pattern document is then cycled through the copier by normal operation. The optical scanner 22 scans the master test pattern document and provides the scanned test pattern as one input to the combiner 26. Meanwhile switch 29 has been automatically or manually moved to the 29b or electronic overlay position 59 so that the test pattern that was previously printed is now provided as a second input to combiner 26. Combiner 26 electronically overlays 59 the test pattern from the test pattern generator 26 over the scanned test pattern from the optical scanner 22. The combination is printed onto a single output document 60 for visual analysis 62 by the user. Ideally, the overlaid test pattern should be identical with the scanned test pattern resulting in what would appear to the operator as a single test pattern print out. However, in practice some tolerance is allowed, thus if the registration is within the allowable tolerance the registration of the automatic handling device is acceptable. If otherwise, the user can adjust the components affecting registration 66 as necessary and repeats the steps described above. Optionally, it may be desirable to mix the digital signals in the combiner 26 so as to produce a difference signal indicating numerically the magnitude and direction of a registration problem of the document

handling system 11. Another test pattern option for determining document registration may be the selection of complimentary or cooperating test patterns. Cooperating test patterns would be designed to measure the registration of the entire document. For example the test pattern overlaid on the copied test pattern need not be identical as described above but could be the second half of a stored image such that when overlaid with the image of the first half the output is the complete image. If the two images do not form the whole image or if the image seam(s) are distorted the user may immediately detect a registration problem and proceed to correct as described above.

[0017] Thus, as described above, an advantage of this invention over other methods is that the user has immediately available a variety of master test designed to measure document registration. Other methods for measuring document registration require expensive and specially constructed preprinted master test documents. With one embodiment of this invention the user may print specific test patterns on specific paper sizes as needed to visually or electronically measure document registration as described above.

[0018] Another advantage of this invention over other methods concerns the logistics of providing master test documents for measuring document registration. The present invention allows the user to print a specific test pattern on a specific size document as needed. Prior art methods using preprinted master test documents require ordering and storing the test documents well in advance of actual required use due to long lead times generally associated with specially constructed test documents. Thus, the present invention allows the user to measure and determine the extent of a registration problem without external special supplies such as preprinted test documents.

#### Claims

1. A registration detection system for measuring document registration in an apparatus having an optical reader adapted to scan a document, the system comprising:

a test pattern generator (24); and

a mixer for combining an output of the test pattern generator with an output of the optical reader (26).

2. A scanner registration detection system according to claim 1, wherein the test pattern generator comprises:

a memory device (25); and

an integrated circuit (IC) board (24a) connected

to the memory device.

3. A scanner registration detection system according to claim 2 wherein the memory device comprises a computer readable data storage medium having at least one test pattern program, the at least one test pattern program preferably comprising crosshair, edged, edged crosshair, grid, and edged grid test pattern programs.

4. A scanner registration detection system according to any one of the preceding claims, wherein the mixer for combining an output of the test pattern generator with an output of the optical reader comprises a digital mixing circuit.

5. A method for determining if a scanner registration problem exists in an apparatus adapted to scan a document, the method comprising the steps of:

printing a first image;

scanning the first image;

combining a first test pattern with the scanned first image; and

providing informative feedback resulting from the step of combining the first test pattern with the scanned first image.

6. A method according to claim 5, wherein the step of printing the first image further comprises the steps of:

retrieving the first test pattern from a memory device;

selecting at least one first medium; and

imaging the first test pattern on the at least one first medium.

7. A method according to claim 5 or 6, wherein the step of combining the first test pattern with the first scanned image further comprises the steps of:

retrieving a digital copy of the first test pattern from a memory device;

displaying the digital copy of the first test pattern onto a second medium; and

displaying the first image scanned onto the second medium.

8. A method according to claim 5, 6 or 7, wherein the step of providing informative feedback resulting

from the step of combining the first test pattern with the scanned first image further comprises the steps of;

measuring a difference between the scanned first image and the first test pattern; and

correlating the difference to indicate the degree of scanner registration alignment.

9. A scanner device registration measuring system for determining a scanner registration problem in a scanner device, the system comprising:

a test pattern generator;


an input document scanning device; and

an image transfer system connected to the test pattern generator and the input document scanning device.


10. A scanner device registration measuring system as in claim 9, wherein the test pattern generator comprises:

a data storage device having at least one data test pattern; and


an integrated circuit board connected to the data storage device.



**FIG. 1**  
**PRIOR ART**



**FIG. 2**  
PRIOR ART



**FIG. 3**






FIG. 4




FIG. 4a





FIG. 5



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 104 161 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
17.04.2002 Bulletin 2002/16

(51) Int Cl.7: **H04N 1/00**

(43) Date of publication A2:  
30.05.2001 Bulletin 2001/22

(21) Application number: **00310090.6**

(22) Date of filing: **14.11.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventor: **Salgado, David L.**  
**Victor, NY 14564 (US)**

(74) Representative: **Rackham, Stephen Neil**  
**GILL JENNINGS & EVERY,**  
**Broadgate House,**  
**7 Eldon Street**  
**London EC2M 7LH (GB)**


(30) Priority: **24.11.1999 US 448805**

(71) Applicant: **Xerox Corporation**  
**Rochester, New York 14644 (US)**

(54) **Measuring scanner registration**

(57) A registration detection system determines a registration problem in an apparatus having an optical reader (22) adapted to scan a document. The system

comprises a test pattern generator (24) and a mixer (26) for combining an output of the test pattern generator (24) with an output of the optical reader (22).



**FIG. 3**

**EP 1 104 161 A3**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 00 31 0090

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 271 096 A (COOK ROBERT L) 14 December 1993 (1993-12-14)	9	H04N1/00
Y	* the whole document *	1-3,10	
A	---	5-8	
X	EP 0 735 738 A (HEWLETT PACKARD CO) 2 October 1996 (1996-10-02)	9	
A	* abstract *	1,5	
Y	EP 0 325 415 A (XEROX CORP) 26 July 1989 (1989-07-26)	1-3,10	
A	* abstract *	5-8	
A	EP 0 501 334 A (SHARP KK) 2 September 1992 (1992-09-02)	1,5,9	
A	Y. MURAKI: "DIAGNOSTICS ALGORITHM FOR IMAGE SCANNER" IBM TECHNICAL DISCLOSURE BULLETIN, vol. 24, no. 4, - 30 September 1981 (1981-09-30) pages 1775-1777, XP002190484 ARMONK (US) * the whole document *	1	
A	ANONYMOUS: "METHOD FOR AUTOMATICALLY COMPARING A PRINTABLE OUTPUT TO A DIGITIZED INPUT" IBM TECHNICAL DISCLOSURE BULLETIN, vol. 34, no. 5, - 31 October 1991 (1991-10-31) pages 55-56, XP000189673 ARMONK (US) * the whole document *	1	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>15 February 2002</b>	Examiner <b>Hazel, J</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (P4C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 31 0090

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-02-2002

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5271096 A	14-12-1993	AU 8327991 A	04-02-1992
		WO 9201264 A1	23-01-1992
EP 0735738 A	02-10-1996	EP 0735738 A2	02-10-1996
		JP 8279876 A	22-10-1996
		US 6016207 A	18-01-2000
EP 0325415 A	26-07-1989	US 4831420 A	16-05-1989
		DE 68915460 D1	30-06-1994
		DE 68915460 T2	15-12-1994
		EP 0325415 A2	26-07-1989
		JP 1216373 A	30-08-1989
		JP 2559835 B2	04-12-1996
EP 0501334 A	02-09-1992	JP 2975437 B2	10-11-1999
		JP 4273650 A	29-09-1992
		DE 69204704 D1	19-10-1995
		DE 69204704 T2	09-05-1996
		EP 0501334 A2	02-09-1992
		US 5267049 A	30-11-1993

EPO FORM P0455

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

This Page Blank (uspto)

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: \_\_\_\_\_**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

***This Page Blank (uspto)***